

ACTION EUROPE®

TECHNICAL
SHEET



CR-1000

ELECTRIC CRIMPING & DECAPPING STATION

DESCRIPTION :

Our CR-1000 crimping station combines adjustable power with reproducible crimping.

- Suitable for all models of closures on the market
- Ergonomic, easy-to-use station
- Recommended for aluminium and steel caps (CTC - Combi PAL)
- Built-in power supply
- Sturdy and reliable
- Light and portable
- Create & develops in France

CHARACTERISTICS & ADVANTAGES :

- Secure, reproducible crimping just by pressing the “start cycle” button.
- Ideally suited for crimping and decapping magnetic steel caps.
- Progressively-adjustable power according to the type of cap and hardness of the seals.
- Fast, easy head changing without tools.
- Does not require the use of compressed air or charging of electrical batteries.
- Fast, easy electric actuator replacement.
- The operator is not subjected to the weight and imprecision of conventional instruments used at arm’s length.



The CR-1000 is very compact, versatile, stable, and allows the crimping and decapping force to be adjusted precisely.

The interchangeable crimping or decapping heads are easily fitted without tools and are especially suited for crimping and decapping aluminium and stainless-steel caps with a diameter of 8, 11, 13, and 20 mm.

Special heads are available for 13 mm and 20 mm flip-off caps.

The force setting can be adjusted progressively using a potentiometer according to the hardness of the seals and the type of caps used.

The CR-1000 is compatible with aluminium standard caps, safety caps used in Headspace, magnetic steel caps, and flip-off caps.

The crimping force is much higher than using hand crimpers fitted with a battery (limited by its life or state of charge).

DESCRIPTION	CAT. No.
Crimptronic CR-1000 electronic crimping station (Complete station less crimping head)	CR-1000
High-performance electronic crimping station fitted with a special actuator 1-year guarantee extension (includes parts and labour) Mode Crimptronic CR-1000 (Complete station less crimping head)	CR-1000GEX
Aluminium shipping case with custom-profiled foam packing	CTA1000



Force adjustable according to the type of caps and seals



Easy to move




Requires only a simple 230 V / 50 Hz supply




Average rate
400 vials / hour



Crimping for all types and sizes of vials



Compact
Can be installed on table or lab bench
H 60 cm x W 16 cm x D 20 cm



Allows crimping and decapping



French manufactured



Machine can be repaired for 10 years



Don't hesitate to contact us for further details



* **Note :** Accessories | Safety covers for crimping/decapping heads.
Whether or not a cover is used does not affect the crimp quality but will allow you to use the unit in complete safety.

OPTIONS COMPATIBILITY						
OPTION	DESCRIPTION	CR-1000	CR-4000	CR-5000	CR-6000	...
Option «A»	LCD display with 5 adjustable levels and total counter		X			
Option «C»	Electric cycle / total counter		X			SC-4000
Option «D»	Two-position sliding guide mounted on ball screw			X		
Option «E»	Special stainless-steel case sealed to IP65 (dust and water jets), crimp head sealing by double O-ring, IP65 touch-sensitive display for adjusting and pre-selecting crimping forces, totalling counter, automatic crimping height adjustment system with a carriage guided using a trapezoidal screw, internal temperature management.			X		
Option «I»	316 L stainless-steel case	X	X	X	X	SC-4000
Option «L»	Wide working area opening. Particularly suitable for using 50 and 100 ml vials, the area is protected by 3 IR sensors		X			SC-4000
Option «T»	Temperature probe		X	X		SC-4000
Option «USB»	Option "USB" Machine control by microprocessor, with USB link Force curves can be saved Configuration and saving of the various force levels according to the type of closure. Statistics and monitoring of the number of crimping and decapping operations performed, the average force applied, usage time Any other functions can be produced upon request (Statistics, operation, display, etc.)		X			
Option «V»	Fan (recommended for intensive use)		X	X		SC-4000
CT-6000	Electrical transport, guidance, and positioning system for automatic cap fitting				X	
Option «R»	Networking using a server for statistical monitoring of manufacturing batches			CR-5000S	CR-6000	
Option «PCD»	Remote control			CR-5000S	CR-6000	RO-4000

TORQUING HEAD FOR SC-4000	CAT. No.
Torquing head for DIN 18 neck	TV18
Torquing head for DIN 20 neck	TV20
Torquing head for DIN 22 neck	TV22
Torquing head for DIN 24 neck	TV24

CRIMPING HEAD	CAT. No.	COVER*
Crimping head for 8 mm Ø caps	TS08	CAO08S
Crimping head for 11 mm Ø caps	TS11	CAO11S
Crimping head for 13 mm Ø caps	TS13	CAO13S
Crimping head for 13 mm Ø overflowing flip-off caps	TS13FLO	CAO13FLOS
Crimping head for 13 mm Ø flip-off with tongue caps	TS13FTU	CAO13FTUS
Crimping head for 13 mm Ø not-overflowing flip-off caps	TS13FS	CAO13FSS
Crimping head for 20 mm Ø caps	TS20	CAO20S
Crimping head for 20 mm Ø overflowing flip-off caps	TS20FLO	CAO20FLOS
Crimping head for 20 mm Ø flip-off with tongue caps	TS20FTU	CAO20FTUS
Crimping head for 20 mm Ø not-overflowing flip-off caps	TS20FS	CAO20FSS
Crimping head for 28 mm Ø caps	TS28	CAO28S
Crimping head for 32 mm Ø caps	TS32	CAO32S
Crimping head for 32 mm Ø overflowing flip-off caps	TS32FLO	CAO32FLOS
Crimping head for 32 mm Ø not-overflowing flip-off caps	TS32FS	CAO32FSS



Add «-I» after the reference of the standard cover to benefit from the stainless steel finish

* **Note :** Accessories | Safety covers for crimping/decapping heads.

Whether or not a cover is used does not affect the crimp quality but will allow you to use the unit in complete safety.

DECAPPING HEAD	CAT. No.	COVER*
Decapping head for crimp-top vials using an 8 mm Ø neck	TD08	CAO08D
Decapping head for crimp-top vials using an 11 mm Ø neck	TD11	CAO11D
Decapping head for crimp-top vials using an 13 mm Ø neck	TD13	CAO13D
Decapping head for crimp-top vials using an 20 mm Ø neck	TD20	CAO20D

HOLDING HEAD FOR CAPS ROLLTRONIC RO-4000	CAT. NO.
Holding head for 13 mm Ø caps	TM-RO-13
Holding head for 13 mm Flip-Off Ø caps (overflowing)	TM-RO-13FLO
Holding head for 13 mm Flip-Off Ø caps (not overflowing)	TM-RO-13FS
Holding head for 13 mm Flip-Off Ø caps (flat surface)	TM-RO-13OVB
Holding head for 20 mm Ø caps	TM-RO-20
Holding head for 20 mm Flip-Off Ø caps (overflowing)	TM-RO-20FLO
Holding head for 20 mm Flip-Off Ø caps (not overflowing)	TM-RO-20FS
Holding head for XXØ caps Manufactured on request (Ø & specificity of the caps)	TM-RO- XX

PRECISION ADAPTOR FOR VIALS ROLLTRONIC RO-4000	CAT. NO.
Precision stainless-steel adaptor for XXØ vials Manufactured on request (Ø & Height of the vials)	AD-RO- XX



Burn both sides of your security cover with the text of your choice !

example :



DON'T HESITATE TO CONTACT US :

Monday to Friday
09h⁰⁰ - 12h⁰⁰
14h⁰⁰ - 18h⁰⁰

ACTION EUROPE
43, rue des Violettes
68390 Sausheim
France

+33 (0) 3 89 45 62 16

Sales Director :
info@actioneurope.fr

General information :
guillaume.gargowitsch@actioneurope.fr

